

1. Body Electrical

Battery	Type		MT model: 55D23L (MF)	AT model: 75D23L (MF)
	Capacity	Reverse capacity	MT model: 99 minutes	AT model: 118 minutes
		Cold cranking ampere	MT model: 356 amperes	AT model: 520 amperes
Combination meter	Speedometer		Electric pulse type	
	Temperature gauge		Thermistor cross coil type	
	Fuel gauge		Resistance cross coil type	
	Tachometer		Electric impulse type	
	Turn signal indicator light		12 V — 1.4 W	
	Charge indicator light		12 V — 1.4 W	
	Oil pressure indicator light		12 V — 1.4 W	
	ABS warning light		12 V — 1.4 W	
	CHECK ENGINE warning light (Malfunction indicator light)		12 V — 1.4 W	
	HI-beam indicator light		12 V — 1.4 W	
	Door open warning light		12 V — 1.4 W	
	Seat belt warning light		12 V — 1.4 W	
	Brake fluid and parking brake warning light		12 V — 1.4 W	
	FWD indicator light		12 V — 1.4 W	
	AIRBAG warning light		12 V — 1.4 W	
	Meter illumination light		12 V — 3.4 W	
	AT OIL TEMP. warning light		12 V — 1.4 W	
Headlight			12 V — 60/55 W (Halogen)	
Front turn signal light/side marker, parking light			12 V — 27 W/8 W	
Front fog light			12 V — 55 W	
Rear combination light		Tail/Stop light	12 V — 8/27 W	
		Turn signal light	12 V — 27 W	
		Back-up light	12 V — 27 W	
License plate light			12 V — 5 W	
High-mount stop light			12 V — 13 W	
Room light			12 V — 8 W	
Spot light			12 V — 8 W	
Luggage room light			12 V — 5 W	
Front wiper motor	Input		12 V — 54 W or less	
Rear wiper motor	Input		12 V — 42 W or less	
Front washer motor	Pump type		Centrifugal	
	Input		12 V — 36 W or less	
Rear washer motor	Pump type		Centrifugal	
	Input		12 V — 36 W or less	
Horn			12 V — 350 Hz	
Accessory socket	Input		12 V — 120 W	
Rear window defogger	Input		12 V — 160 W	
	Indicator light		12 V — 50 mA	
Cargo socket	Input		12 V — 120 W	