

### 9. Transfer

Transfer clutch	Hydraulic multi-plate clutch
Drive & driven plate number of transfer clutch	5
Control method	Electronic, hydraulic type
Lubricant	The same Automatic transmission fluid used in automatic transmission
1st reduction gear ratio	1.000 (53/53)

### 10. Final Reduction

Front final gear ratio	4.444 (40/9)																		
Lubrication oil	<p style="text-align: center;">ITEM</p> <p style="text-align: center;">• Front differential gear oil</p> <p style="text-align: center;">API Classification</p> <p style="text-align: center;">GL - 5</p> <p style="text-align: center;">SAE Viscosity No. and Applicable Temperature</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>(°C)</td> <td>-30</td> <td>-26</td> <td>-15</td> <td>-5</td> <td>0</td> <td>15</td> <td>25</td> <td>30</td> </tr> <tr> <td>(°F)</td> <td>-22</td> <td>-15</td> <td>5</td> <td>23</td> <td>32</td> <td>59</td> <td>77</td> <td>86</td> </tr> </table> <p style="text-align: right;">H3M1235A</p>	(°C)	-30	-26	-15	-5	0	15	25	30	(°F)	-22	-15	5	23	32	59	77	86
(°C)	-30	-26	-15	-5	0	15	25	30											
(°F)	-22	-15	5	23	32	59	77	86											
Front differential oil capacity	1.2 ℓ (1.3 US qt, 1.1 Imp qt)																		

**MEMO:**