

1. Body Electrical

Battery	Type		MT model: 55D23L (MF) AT model: 75D23L (MF)
	Capacity	Reverse capacity	MT model: 100 minutes AT model: 120 minutes
		Cold cranking ampere	MT model: 430 amperes AT model: 520 amperes
Combination meter	Speedometer		Eddy current type
	Temperature gauge		Thermistor cross coil type
	Fuel gauge		Resistance cross coil type
	Tachometer		Electric impulse type
	Turn signal indicator light		12 V — 1.4 W
	Charge indicator light		12 V — 1.4 W
	Oil pressure indicator light		12 V — 1.4 W
	A.B.S. warning light		12 V — 1.4 W
	CHECK ENGINE warning light		12 V — 1.4 W
	HI-beam indicator light		12 V — 3.4 W
	Door open warning light		12 V — 1.4 W
	Seat belt warning light		12 V — 1.4 W
	Brake fluid and parking brake warning light		12 V — 3.4 W
	FWD warning light		12 V — 1.4 W
	AIRBAG warning light		12 V — 1.4 W
	Meter illumination light		12 V — 3.4 W
AT OIL TEMP. warning light		12 V — 1.4 W	
Headlight			12 V — 60/55 W (Halogen)
Front turn signal light			12 V — 27 W
Side turn light			12 V — 3.8 W
Side marker/Parking light			12 V — 3.8 W
Rear combination light	Tail/Stop light		12 V — 8/27 W
	Turn signal light		12 V — 27 W
	Back-up light		12 V — 27 W
License plate light			12 V — 3.8 W
High-mount stop light			Sedan: 12 V — 18 W Wagon: 12 V — 13 W
Room light			12 V — 8 W
Spot light			12 V — 8 W
Trunk room light			12 V — 5 W
Luggage room light			12 V — 5 W
Selector lever illumination light			12 V — 1.7 W