

1. Body Electrical

Battery	Type		MT model: 55D23L (MF)	AT model: 75D23L (MF)
	Capacity	Reverse capacity	MT model: 100 minutes	AT model: 120 minutes
		Cold cranking ampere	MT model: 430 amperes	AT model: 520 amperes
Combination meter	Speedometer		Electric pulse type	
	Temperature gauge		Thermistor cross coil type	
	Fuel gauge		Resistance cross coil type	
	Tachometer		Electric impulse type	
	Turn signal indicator light		12 V — 1.4 W	
	Charge indicator light		12 V — 1.4 W	
	Oil pressure indicator light		12 V — 1.4 W	
	ABS warning light		12 V — 1.4 W	
	CHECK ENGINE warning light (Malfunction indicator light)		12 V — 1.4 W	
	HI-beam indicator light		12 V — 3.4 W	
	Door open warning light		12 V — 1.4 W	
	Seat belt warning light		12 V — 1.4 W	
	Brake fluid and parking brake warning light		12 V — 3.4 W	
	FWD indicator light		12 V — 1.4 W	
	AIRBAG warning light		12 V — 1.4 W	
Meter illumination light		12 V — 3.4 W		
AT OIL TEMP. warning light		12 V — 1.4 W		
Headlight		12 V — 60/55 W (Halogen)		
Front fog light		12 V — 55 W		
Front turn signal light		12 V — 27 W		
Side turn signal light		12 V — 3.8 W		
Side marker/Parking light		12 V — 3.8 W		
Rear combination light	Tail/Stop light		12 V — 8/27 W	
	Turn signal light		12 V — 27 W	
	Back-up light		12 V — 27 W	
License plate light		12 V — 3.8 W		
High-mount stop light		Sedan: 12 V — 18 W	Wagon: 12 V — 13 W	
Room light		12 V — 8 W		
Spot light		12 V — 8 W		
Trunk room light		12 V — 5 W		
Luggage room light		12 V — 5 W		
Front wiper motor	Input		12 V — 54 W or less	
Rear wiper motor	Input		12 V — 42 W or less	
Front washer motor	Pump type		Centrifugal	
	Input		12 V — 36 W or less	
Rear washer motor	Pump type		Centrifugal	
	Input		12 V — 36 W or less	
Horn		12 V — 350 Hz		
Accessory socket	Input		12 V — 120 W	
Rear window defogger	Input		12 V — 160 W	
	Indicator light		12 V — 50 mA	
Cargo socket	Input		12 V — 120 W	