

2. Station Wagon

2. ENGINE

Engine type	Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine	
Valve arrangement	Overhead camshaft type	
Bore x Stroke	mm (in)	96.9 x 75.0 (3.815 x 2.953)
Displacement	cm ³ (cu in)	2,212 (135.0)
Compression ratio	9.7	
Firing order	1 — 3 — 2 — 4	
Idle speed at Park/Neutral position	rpm	700
Maximum output	kW (HP)/rpm	101 (135)/5,400
Maximum torque	N.m (kg-m, ft-lb)/rpm	190 (19.4, 140)/4,400

3. ELECTRICAL

Ignition timing at idling speed	BTDC/rpm	20°/700
Spark plug	Type and manufacturer	CHAMPION: RC10YC4 (Standard) NGK: BKR6E-11 NIPPONDENSO: K20PR-U11
Generator	12V — 85A	
Battery	Reserve capacity	min 100
	Cold cranking amperes	amp. 490

10. WEIGHT

Model		AWD	
		POST	
		4AT	
Curb weight (C.W.)	Front	kg (lb)	748 (1,650)
	Rear	kg (lb)	619 (1,365)
	Total	kg (lb)	1,367 (3,015)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	936 (2,065)
	Rear	kg (lb)	989 (2,180)
	Total	kg (lb)	1,925 (4,245)

NOTE:
Includes the weights of power window, power door lock and air conditioning in the curb weight.