

SCHEDULE

Periodic Maintenance Services

2. Schedule SA07682

A: MAINTENANCE SCHEDULE 1 SA07682G24

		MAINTENANCE INTERVAL																	Remarks
		[Number of months or km (miles), whichever occurs first]																	
Months		3	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	
× 1,000 km		4.8	12	24	36	48	60	72	81.4	96	108	120	132	144	156	168	180	192	
× 1,000 miles		3	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	
1	Engine oil	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
2	Engine oil filter	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
3	Spark plugs					R				R				R				R	
										R								R	
4	Drive belt(s)					I				I				I		R			
5	Camshaft Drive belt					I				I				I		R		For 2.5 L Note (1)	
6	Valve clearance															I			
8	Fuel line					(I)				(I)				(I)				I	
9	Fuel filter					(R)				(R)				(R)				R	
10	Air cleaner element					R				R				R				R	
11	Cooling system					I				I				I				I	
12	Coolant					R				R				R				R	
13	Clutch system			I		I		I		I		I		I		I		I	
14	Transmission oil					I				I				I				I	
15	ATF					I				I				I				I	
16	Front & rear differential oil					I				I				I				I	
17	Brake line			I		I		I		I		I		I		I		I	
18	Brake fluid					R				R				R				R	
19	Disc brake pads & discs					I				I				I				I	
20	Brake linings and drums					I				I				I				I	
21	Parking brake			I		I		I		I		I		I		I		I	
22	Suspension			I		I		I		I		I		I		I		I	
23	Wheel bearing									(I)								(I)	
24	Axle boots & joints			I		I		I		I		I		I		I		I	
25	Tire rotation		I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	
26	Steering system (Power steering)			I		I		I		I		I		I		I		I	
27	Supplement restraint system																		

Symbols used:

R: Replace

I: Inspection

(R) or (I): Recommended service for safe vehicle operation.

NOTE:

(1) Periodic inspection and replacement of the camshaft drive chains on the 3.0 liter models are not required.

(2) This inspection is not required to maintain emission warranty eligibility and it does not affect the manufacturer's obligations under EPA's in-use compliance program.

(3) When the vehicle is used in extremely dusty conditions, the air cleaner element should be replaced more often.

(4) ATF filter is maintenance free part. ATF filter needs replacement, when it has physically damaged or ATF leaked.

(5) A tire should be replaced when the tread wear indicator appears as a solid band across the tread. The indicators appear when the remaining tread has been worn to 1.6 mm (0.063 in) or less.

SCHEDULE

Periodic Maintenance Services

B: MAINTENANCE SCHEDULE 2 SA07682G25

Item	Every	Repeat short distance drive	Repeat rough/muddy road drive	Extremely cold weather area	Salt or other corrosive used or coastal area	High humidity or mountain area	Repeat tow-ing trailer
Engine oil	3.75 months	R		R			R
	6,000 km						
	3,750 miles						
Engine oil filter	3.75 months	R		R			R
	6,000 km						
	3,750 miles						
Fuel filter	15 months				I		
	24,000 km						
	15,000 miles						
Fuel line	15 months				I		
	24,000 km						
	15,000 miles						
Transmission oil	15 months						R
	24,000 km						
	15,000 miles						
ATF	15 months						R
	24,000 km						
	15,000 miles						
Front & rear differential oil	15 months						R
	24,000 km						
	15,000 miles						
Brake line	15 months	I	I		I		I
	24,000 km						
	15,000 miles						
Brake fluid	15 months					R	
	24,000 km						
	15,000 miles						
Disc brake pads & discs	15 months	I	I		I		I
	24,000 km						
	15,000 miles						
Brake linings and drums	15 months	I	I		I		I
	24,000 km						
	15,000 miles						
Parking brake	15 months	I	I		I		I
	24,000 km						
	15,000 miles						
Suspension	7.5 months		I	I	I		I
	12,000 km						
	7,500 miles						
Axle boots & joints	7.5 months	I	I	I	I		I
	12,000 km						
	7,500 miles						
Steering system (Power steering)	7.5 months	I	I	I	I		I
	12,000 km						
	7,500 miles						