# SCHEDULE

# 2. Schedule

# A: MAINTENANCE SCHEDULE 1

		MAINTENANCE INTERVAL [Number of months or km (miles), whichever occurs first]																	
	Months	3	7.5	15	22.5	30	37.5	ber o	52.5	ns or	67.5		wniche 82.5	90	97.5	105	112.5	120	Remarks
	× 1,000 km	4.8	12	24	36	48	60	72	81.4	96	108	120	132	144	156	168	180	192	Kemarks
	× 1,000 km × 1,000 miles	3	7.5	15		30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	
1	Engine oil	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
2	Engine oil filter	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
3	Spark plugs					R				R				R				R	For 2.5 L
	<b>5</b> 1 1 1/1									R								R	For 3.0 L
4	Drive belt(s)									I				I		R			E 0.51
5	Camshaft Drive belt					I				ı				I		R			For 2.5 L Note (1)
6	Fuel line					(I)				(I)				(I)				<u> </u>	Note (2)
7	Fuel filter					(R)				(R)				(R)				R	Note (2)
8	Air cleaner element					R				R				R				R	Note (3)
9	Cooling sys- tem					I				I				I				I	
10	Coolant					R				R				R				R	
11	Clutch sys- tem			I		I		I		I		I		I		I		I	
12	Transmis- sion oil					ı				ı				I				I	
13	ATF					ı				ı				I				I	Note (4)
14	Front & rear differential oil					I				I				I				ı	
15	Brake line			I		ı		Ι		ı		I		I		I		I	
16	Brake fluid					R				R				R				R	
17	Disc brake pads & discs					I				I				I				I	
18	Parking brake			I		I		I		I		I		I		I		I	
19	Suspension			I		I		I		I		ı		I		I		I	
20	Wheel bear- ing									(I)								(I)	
21	Axle boots & joints			I		I		I		I		I		I		I		I	
22	Tire rotation		I	ı	I	I	I	ı	I	I	I	I	I	I	I	I	I	I	Note (5)
23	Steering system (Power steering)			I		I		I		I		I		-		I		I	
24	Supple- ment restraint system	Inspect every 10 years.																	

## **SCHEDULE**

### PERIODIC MAINTENANCE SERVICES

Symbols used:

R: Replace

I: Inspection

(R) or (I): Recommended service for safe vehicle operation.

- NOTE: (1) Periodic inspection and replacement of the camshaft drive chains on the 3.0 liter models are not required.
- (2) This inspection is not required to maintain emission warranty eligibility and it does not affect the manufacturer's obligations under EPA's in-use compliance program.
- (3) When the vehicle is used in extremely dusty conditions, the air cleaner element should be replaced more often.
- (4) ATF filter is maintenance free part. ATF filter needs replacement, when it has physically damaged or ATF leaked.
  (5) A tire should be replaced when the tread wear indicator appears as a solid band across the tread. The indicators appear when the remaining tread has been worn to 1.6 mm (0.063 in) or less.

## **SCHEDULE**

# **B: MAINTENANCE SCHEDULE 2**

Item	Every	Repeat short distance drive	Repeat rough/muddy road drive	Extremely cold weather area	Salt or other corrosive used or coastal area	High humid- ity or moun- tain area	Repeat tow- ing trailer
Engine oil	3.75 months	R		R			R
İ	6,000 km	]					
İ	3,750 miles	1					
Engine oil filter	3.75 months	R		R			R
İ	6,000 km	]					
İ	3,750 miles	]					
Fuel filter	15 months				I		
İ	24,000 km						
İ	15,000 miles						
Fuel line	15 months				I		
<b>†</b>	24,000 km	1					
†	15,000 miles	1					
Transmission oil	15 months						R
İ	24,000 km						
İ	15,000 miles						
ATF	15 months						R
İ	24,000 km	1					
İ	15,000 miles	1					
Front & rear differ-	15 months						R
ential oil	24,000 km	1					
t	15,000 miles	1					
Brake line	15 months	I	ı		I		ı
İ	24,000 km	1					
İ	15,000 miles	1					
Brake fluid	15 months					R	
İ	24,000 km	1					
İ	15,000 miles	1					
Disc brake pads &	15 months	ı	ı		I		ı
discs	24,000 km	1					
İ	15,000 miles	1					
Parking brake	15 months	ı	ı		I		ı
	24,000 km	1					
İ	15,000 miles	1					
Suspension	7.5 months		ı	ı	I		ı
•	12,000 km	1					
t	7,500 miles	1					
Axle boots & joints	7.5 months	ı	I	I	ı		ı
	12,000 km	1					
t	7,500 miles	1					
Steering system	7.5 months	ı	I	I	ı	1	ı
	12,000 km	· ·			·		,
(Power steering)	12.000 KM						