FRONT WIPER AND WASHER

Wiper and Washer Systems

1. Front Wiper and Washer

A: DESCRIPTION

1. FRONT WIPER


1) The front wiper is of a tandem type featuring wide wiping area. The blade is installed to the arm by means of U-hook joint to improve serviceability.

2) The front wiper operates in the HI and LOW speed modes and the INTERMITTENT mode.

The operation modes can be selected by turning the wiper switch incorporated in the combination switch.

3) In the INTERMITTENT mode, the intermittent unit installed behind the combination switch controls the front wiper operation interval.

4) The front wiper system uses a modular construction in which the wiper motor forms an integral part of the linkage. The motor is installed on the body through rubber mounting.



WW-00038

FRONT WIPER AND WASHER

2. FRONT WASHER SYSTEM

1) The washer system consists of a washer tank, a motor and pump unit, and a pair of nozzles.

2) The washer tank is installed at the front of the strut mount on the left side of the engine compartment.

3) The washer motor and pump unit is installed at the bottom of the washer tank.

- 4) The washer nozzles are installed on the hood. Each nozzle is a diffusion nozzle.
- 5) Each washer nozzle is provided with a check valve which is located just below it.

3. SPECIFICATION

Washer tank	Capacity			4.0 liters (4.2 US qt, 3.5 imp qt)
Wiper motor	Rated voltage			12 V
	No-load current			4 A or less
	Speed [at 2.0 N·m (20 kg cm 17 in-lb)]		HIGH	72 ± 6 rpm
			LOW	47 ± 5 rpm
	Locked rotor character- istics	HIGH	Torque	29.4 N m (300 kg cm 2.2 ft-lb)
			Current	36 A or less
		LOW	Torque	34.3 N m (350 kg cm 2.5 ft-lb)
			Current	31.5 A or less
Wiper blade		Driver sic	le	550 mm (21.65 in)
		Passenger side		500 mm (19.69 in)