### **20.General Diagnostic Table** A: INSPECTION

#### **1. MANUAL TRANSMISSION**

| Symptom                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Possible cause                                                                                                                                                                                                                                                      | Corrective action                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| 1. Gears are difficult to intermesh.<br>NOTE:<br>The cause for difficulty in shifting gears<br>can be classified into two kinds: One is a<br>defective gear shift system and the other<br>is defective transmission. However, if the<br>operation is heavy and engagement of the<br>gears is difficult, a defective clutch disen-<br>gagement may also be responsible.<br>Check whether the clutch is correctly<br>functioning, before checking the gear shift<br>system and transmission. | (a) Worn, damaged or burred chamfer at<br>internal spline of the sleeve and reverse<br>driven gear                                                                                                                                                                  | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (b) Worn, damaged or burred chamfer of gear spline                                                                                                                                                                                                                  | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (c) Worn or scratched bushings                                                                                                                                                                                                                                      | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (d) Incorrect contact or wear between synchronizer ring and gear cone                                                                                                                                                                                               | Rectify or replace.                      |
| 2. Gear slip-out                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (a) Defective pitching stopper adjustment                                                                                                                                                                                                                           | Adjust.                                  |
| • Gear slips out when coasting on rough                                                                                                                                                                                                                                                                                                                                                                                                                                                    | (b) Loose engine mounting bolts                                                                                                                                                                                                                                     | Tighten or replace.                      |
| road.<br>• Gear slips out during acceleration.                                                                                                                                                                                                                                                                                                                                                                                                                                             | (c) Worn fork shifter, broken shifter fork rail spring                                                                                                                                                                                                              | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (d) Worn or damaged ball bearing                                                                                                                                                                                                                                    | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (e) Excessive clearance between splines<br>of synchronizer hub and synchronizer<br>sleeve                                                                                                                                                                           | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (f) Worn tooth step of synchronizer hub<br>(caused by slip-out of 3rd gear)                                                                                                                                                                                         | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (g) Worn 1st driven gear and driven shaft                                                                                                                                                                                                                           | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (h) Worn 2nd driven gear and bushing                                                                                                                                                                                                                                | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (i) Worn 3rd drive gear and needle bear-<br>ing                                                                                                                                                                                                                     | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (j) Worn 3rd drive gear and needle bear-<br>ing                                                                                                                                                                                                                     | Replace.                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (k) Worn reverse idler gear and bushing                                                                                                                                                                                                                             | Replace.                                 |
| 3. Noise emitted from transmission                                                                                                                                                                                                                                                                                                                                                                                                                                                         | (a) Insufficient or improper lubrication                                                                                                                                                                                                                            | Lubricate with specified oil or replace. |
| NOTE:<br>If a noise is heard when the vehicle is<br>parked with its engine idling and if a noise<br>ceases when the clutch is disengaged, it<br>may be considered that the noise is com-<br>ing from the transmission.                                                                                                                                                                                                                                                                     | (b) Worn or damaged gears and bearings<br>NOTE:<br>If the trouble is only wear of the tooth sur-<br>faces, merely a high roaring noise will oc-<br>cur at high speeds, but if any part is<br>broken, rhythmical knocking sound will be<br>heard even at low speeds. | Replace.                                 |

#### 2. DIFFERENTIAL

| Symptom                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Possible cause                                                                                                                                      | Corrective action                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ol> <li>Broken differential (case, gear, bear-<br/>ing, etc.)</li> <li>NOTE:</li> <li>Noise will occur, and eventually the differ-</li> </ol>                                                                                                                                                                                                                                                                                                                                                                            | (a) Insufficient or improper oil                                                                                                                    | Disassemble the differential and replace<br>broken components. At the same time<br>check other components for any trouble,<br>and replace if necessary. |
| ential will not be able to operate due to<br>broken pieces obstructing the gear revo-<br>lution.                                                                                                                                                                                                                                                                                                                                                                                                                          | (b) Use of vehicle under severe condi-<br>tions such as excessive load and<br>improper use of the clutch                                            | Readjust the preload and backlash of the bearing, and the contact surface of gear.                                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (c) Improper adjustment of taper roller bearing                                                                                                     | Adjust.                                                                                                                                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (d) Improper adjustment of the drive pin-<br>ion and the hypoid driven gear                                                                         | Adjust.                                                                                                                                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (e) Excessive backlash of a vehicle under<br>severe operating conditions due to worn<br>differential side gear, washer or differen-<br>tial pinion. | Add recommended oil to the specified level. Do not use vehicle under severe operating conditions.                                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (f) Loose hypoid driven gear tightening bolts                                                                                                       | Tighten.                                                                                                                                                |
| 2. Differential and hypoid gear noises                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | (a) Insufficient oil                                                                                                                                | Lubricate.                                                                                                                                              |
| Troubles of the differential and hypoid<br>gear always appear as noise problems.<br>Therefore noise is the first indication of<br>trouble. However, noises from the engine,<br>muffler, tire, exhaust gas, bearing, body,<br>etc. are easily mistaken for the differential<br>noise. Pay special attention to the hypoid<br>gear noise because it is easily confused                                                                                                                                                      | (b) Improper adjustment of hypoid driven gear and drive pinion                                                                                      | Check the tooth contact.                                                                                                                                |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (c) Worn teeth of hypoid driven gear and drive pinion                                                                                               | Replace as a set.<br>Readjust the bearing preload.                                                                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | (d) Loose roller bearing                                                                                                                            | Readjust the backlash of the hypoid driven gear to drive pinion, and check the tooth contact.                                                           |
| with other gear noises. There are the fol-<br>lowing four kinds of noises.                                                                                                                                                                                                                                                                                                                                                                                                                                                | (e) Distorted hypoid driven gear or differ-<br>ential case                                                                                          | Replace.                                                                                                                                                |
| <ul> <li>Gear noise when driving:<br/>If noise increases as the vehicle speed<br/>increases, it may be due to insufficient<br/>gear oil, incorrect gear engagement,<br/>damaged gears, etc.</li> <li>Gear noise when coasting:<br/>Damaged gears due to misadjusted bear-<br/>ings and incorrect shim adjustment.</li> <li>Bearing noise when driving or coast-<br/>ing:<br/>Cracked, broken or damaged bearings</li> <li>Noise mainly when turning:<br/>Noise from differential side gear, differen-<br/>time</li> </ul> | (f) Worn washer and differential pinion<br>shaft                                                                                                    | Replace.                                                                                                                                                |
| tial pinion or differential pinion shaft, etc.                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                     |                                                                                                                                                         |

## **CLUTCH SYSTEM**

# CL

|     |                           | Page |
|-----|---------------------------|------|
| 1.  | General Description       | 2    |
| 2.  | Clutch Disc and Cover     |      |
| 3.  | Flywheel                  |      |
| 4.  | Release Bearing and Lever | 14   |
| 5.  | Operating Cylinder        |      |
| 6.  | Master Cylinder           |      |
| 7.  | Clutch Pipe and Hose      |      |
| 8.  | Clutch Fluid              |      |
| 9.  | Clutch Fluid Air Bleeding |      |
| 10. | Clutch Pedal              | 23   |
| 11. | Clutch Switch             |      |
| 12. | General Diagnostic Table  |      |
|     |                           |      |